

Blueskin® Adhesive

for Blueskin® SA Membranes

Physical Properties

-Color	Blue	-Service Temp	Minus 40°F to 158°F
-Solids by Weight		-Application Temp	Minus 12°F to 104°F
-Weight	35%	-Flammability	
-Coverage	6 lbs./gal. U.S. (approx.) 80 to 250 ft ² /gal. U.S. depending on porosity and texture of surface.	Wet	Flammable
		Dry	Burns
-Drying Time			
Initial Set	30 minutes		
Set Through	2 hours		
-Maximum V.O.C.	450 grams/liter		

Description

Blueskin® Adhesive is a quick drying, rubber based adhesive designed to enhance the adhesion of **Blueskin® SA** membranes.

Features

- Quick setting.
- Aggressive tack provides for superior adhesion of membrane.
- Suitable for application at normal and low temperatures.
- Easily applied.

Uses

Used as an adhesive for self-adhesive membranes such as **Blueskin® SA, WP 200 or PE 200 HT** when applied to masonry, concrete, wood, gypsum board, Dens Glass Gold and metal surfaces.

Blueskin® Adhesive is the surface prep of choice on above grade applications of self-adhered membranes where a quick setting, aggressive tack, solvent based low temperature product is required.

Limitations

Solvent in product attacks polystyrene insulation. Avoid use where solvent odors may taint food or other susceptible products.

Packaging

Blueskin® Adhesive is packaged in 5 gallon pails (contents 3.7L).

Preparation

Surfaces must be dry and free from dust, dirt, grease, oil or other foreign matter.

Application

Blueskin® Adhesive: Apply by brush, roller or spray. Rollers should have a heavy nap of natural material such as lamb's wool. Allow adhesive to dry for 30 minutes before applying membrane.

Coated surfaces not covered by membrane during the working day must be recoated.

Clean Up

Use mineral spirits.

Caution

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPORS MAY CAUSE FLASH FIRE.

Contains hexane, acetone, and methanol. Vapors may ignite explosively. Keep away from heat, sparks, and flame. Vapors may cause flash fire. Do not smoke. Extinguish all flames and pilot lights; turn off all stoves, heaters, electric motors, and other sources of ignition during use and until all vapors are gone. Do not heat container or store at temperatures greater than 120°F. For exterior use only; CLOSE AIR INTAKES until solvents dissipate. Contains volatile solvents that might contaminate potable water. Close container after each use. **DANGER! HARMFUL OR FATAL IF SWALLOWED!** If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY! May be harmful if absorbed through skin. Use protective measures to avoid contact with eyes and skin. In case of eye contact, open eyelids wide and flush immediately with plenty of water for at least 15 minutes. GET MEDICAL ATTENTION! **USE ONLY WITH ADEQUATE VENTILATION!** Avoid breathing of vapor. If you experience eye watering, headaches or dizziness, leave area or increase fresh air or wear respirator (NIOSH/MSHA TC 23°C or equal). Repeated and prolonged occupational exposure to solvents can result in permanent brain and nervous system damage. **KEEP OUT OF REACH OF CHILDREN.**

Limited Warranty

We, the manufacturer, warranty only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will replace at no charge any product proved to be defective within 12 months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. **DISCLAIMER OF WARRANTIES:** The Limited Warranty is IN LIEU OF any other warranties express or implied including but not limited to any implied warranty of MERCHANTABILITY or fitness for a particular purpose, and we, the manufacturer, shall have no further liability of any kind including liability for consequential or incidental damages resulting from any defects or any delays caused by replacement or otherwise.

<>